# **CONTAINER SPECIFICATIONS**

# **DRY CARGO CONTAINERS**

### DIMENSIONS



	Cont	ainer We	ight	lı	nterior M	easureme	ent	Door Open		
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width	Height	Capacity (m³)	Width (m)	Height (m)	
20 ft	24,000	2,370	21,630	5.898	2.352	2.394	33.20	2.343	2.280	
40 ft	30,480	4,000	26,480	12.031	2.352	2.394	67.74	2.343	2.280	

## • CHARACTERISTICS

Manufactured from either Aluminium or steel, they are suitable for most types of cargo / general cargo. Aluminium containers have a slightly larger payload than steel, and steel containers have a slightly larger internal cube

# REFRIGERATED CONTAINERS

## DIMENSIONS



	Cont	ainer We	ight	lı	Interior Measurement				Open
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width	Height (m)	Capacity (m <sup>3</sup> )	Width	Height (m)
20 ft 40 ft	24,000 30,480	3,050 4,520	20,950 25,960	5.449 11.690	2.290 2.250	2.244 2.247	26.70 57.10	2.276 2.280	2.261 2.205

#### CHARACTERISTICS

Recommended for delicate cargo. Bottom-air delivery system ensures refrigerated cargo reaches its destination in optimum condition.

# **OPEN TOP CONTAINERS**

## DIMENSIONS



	Container Weight			lı	nterior M	Door Open			
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width	Height	Capacity (m <sup>3</sup> )	Width (m)	Height
20 ft 40 ft	24,000 30,480	2,580 4,290	21,420 26.190	5.629 11.763	2.212 2.212	2.311 2.311	32.00 65.40	2.330 2.330	2.263 2.263

#### CHARACTERISTICS

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulky cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The container doors can be removed to make the stuffing of cargo more convenient. Manufactured from steel

# **FLAT RACK CONTAINERS**

## DIMENSIONS



	Con	tainer We	ight	Interior Measurement					
Туре	Gross Tare Net		Length Width		Height (m)	Capacity (m <sup>3</sup> )			
20 ft	30,480	2,900	27,580	5.624	2.236	2.234	27.90		
40 ft	34,000	5,870	28,130	11.786	2.236	1.968	51.90		

#### • CHARACTERISTICS

Flatracks are especially suited to heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery There are collapsible and non-collapsible containers with or without walls. Manufactured from steel.

# **GARMENT CONTAINERS**

# DIMENSIONS



	Con	tainer We	ight	li	nterior M	easuremo	ent	Door Open		
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height	Capacity (m <sup>3</sup> )	Width (m)	Height	
20 ft 40 ft	24,000 30,480	2,240 3,885	21,760 26.595	5.898 12.031	2.352 2.352	2.394 2.394	33.20 67.74	2.343 2.343	2.280 2.280	
40 It	00,400	0,000	20,000	12.001	L.00L	L.007	01.14	2.010	L.200	

# CHARACTERISTICS

Use for all kinds of garment. The containers are specially designed for garment product and related industry. There are some options of using a string or bar system or a combination of both. The containers allow increased flexibility, greater load Internal Capacity and savings on transportation and handling cost.

## **HIGH CUBE CONTAINERS**

# DIMENSIONS



	Container Weight			lı	nterior M	Door Open			
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m <sup>3</sup> )	Width (m)	Height
40 ft	30,480	3,980	26,500	12.031	2.352	2.698	76.30	2.340	2.585
45 ft	30,480	4,800	25,680	13.544	2.352	2.698	86.00	2.340	2.585

#### • CHARACTERISTICS

With high cube containers, you gain an extra foot in height compared with general-purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in steel and aluminium.